

APPARATUS AND METHOD FOR FILTERING FLUIDS

Cross-Reference to Related Applications

This application claims the benefit of priority of U.S. Application No.
5 60/443,429 filed January 29, 2003 and U.S. Application No. 60/502,383 filed
September 12, 2003, both of which are incorporated herein by reference.

Background of the Invention

The present invention relates to the filtering of particulates from fluids,
10 particularly the removal of solids from water, using compressible filter media in a
compressible housing.

Prior art techniques using compressible media have relied on
mechanically actuated plates to externally compress filter media.

For example, U.S. Pat. No. 5,248,415 to Masuda et al. discloses the use
15 of fibrous filter media compressed by a movable bottom plate in a bottom-up
filtration apparatus.

U.S. Patent Application Publication No. US2003/0111431 discloses
fibrous filter media compressed by a movable top plate in a bottom-up filtration
apparatus. U.S. Pat. No. 4,776,962 discloses a fibrous filter media compressed
20 by a movable top plate in a downflow filtration apparatus.

In such prior art apparatuses, the movable plate compresses the filter
media within rigid containment walls during filtration and provides compression
across the entire filter media bed. Compression of the media increases the

filtering performance measured as percent removal and removal of smaller particulates; however, particulate rapidly builds up in the initial portion of the media bed and reduces the filter operation time. Filtering efficiency progressively decreases as a result of the particulate accumulation, and eventually filtering must be stopped to wash and dislodge the solid build up. The movable plate pressed against the media further inhibits the capacity of the initial portion of the media bed to remove particulates resulting in shorter filter operation time and less solid removal per unit of filter media. The washing operation requires that the movable plate be retracted so that air and washing fluid may be directed through the media to scrub and dislodge the solids. The media is re-compressed with the movable plate when filtering is restarted. The movable plates require close tolerance with the rigid containment walls to retain filter media and maintain efficient filter and backwashing operations.

Accordingly, there is a need for a filter apparatus and method that provides efficient filtration with compressed media that improves particulate capture with longer filter operation times, but eliminates the need for mechanically movable plates, close tolerance containment walls and associated mechanisms.

Summary of the Invention

The present invention answers these needs by providing a filter apparatus with a movable filter media housing containing compressible filter media. In one embodiment the filter media housing is a flexible housing material. In other

embodiments, the filter media housing may include hinged container walls, sliding mechanisms or similar movable housings for inwardly compressing filter media within the housing.

5 In an embodiment of the invention, a flexible housing houses compressible filter media within an open inner fluid retaining space of a filter apparatus. As the hydrostatic pressure of unfiltered fluid surrounding the housing exceeds the pressure within the housing, the housing and media therein are compressed. Different initial compression and corresponding particle size capture levels are achieved with different initial open inner fluid volumes.

10 In further embodiments of the invention, a first portion of the compressible media within the flexible housing is uncompressed by the filter media housing while a second portion of the media is compressed by the outer housing. In various embodiments a gap is also provided above the loose, uncompressed portion of the filter media to maximize the uncompressed state of the first portion.

15 It is an object of the invention in such embodiments to provide at least two different compression zones so that the fluid being filtered achieves greater penetration through the uncompressed filter media portion to maximize particulate removal deeper in the filter media.

In embodiments of the invention, it is an object of the invention to

20 compress the filter media within the filter media housing with the outer surrounding fluid being filtered.

It is a further object of the invention to provide for washing of compressible media without the need for mechanically movable plates or similar components through flexible outward expansion of the housing during washing of the media.

5 In another embodiment of the invention, a compressible filter media of multi-component fibers is provided for use within the flexible housing of the filter media. The specific gravity, resilience, chemical resistance, stiffness, and filtering performance of the compressible media can be adjusted to the fluid and filtering needs with the use of multi-component fibers.

10 In one embodiment, the compressible filter media comprises fibers with a nylon inner core and polypropylene sheath. In such embodiment, the fibrous lumps have low resilience and lower specific gravity.

In another embodiment, the compressible filter media comprises fibers with a polyester inner core and polypropylene sheath. In such embodiment, the fibrous lumps are heavier and more resilient.

15 In still other embodiments of the invention, a plurality of filter apparatuses of the present invention may be used to filter large amounts of fluid, such as in a basin or other large container within which the plurality of apparatuses are utilized.

20 **Brief Description of the Drawings**

FIG. 1 is a schematic cross-sectional view of a single filter apparatus of the present invention showing a flexible housing for containing filter media in an embodiment of the present invention.

FIG. 2 is a schematic cross-sectional view of a filter apparatus of the present invention during initial filling with fluid to be filtered.

FIG. 3 is a schematic cross-sectional view of a filter apparatus of the present invention as the hydraulic head becomes greater upstream than in the downstream flow and the hydrostatic pressure of the unfiltered fluid compresses the flexible housing in an embodiment of the invention.

FIG. 4 is a schematic cross-sectional view of a filter apparatus of the present invention as influent level reaches an optional overflow pipe in an embodiment of the invention.

FIG. 5 is a schematic cross-sectional view of a filter apparatus of the present invention during backwash operation in an embodiment of the invention.

FIG. 6 is a schematic view of fiber being reduced from spools and bound for cutting into fiber media bundles in an embodiment of the invention.

FIG. 7 is a front perspective view of a filter media bundle in an embodiment of the invention.

FIG. 8 is a cross-sectional view of a filter media element including a hog ring/binding wire crimping and holding the center of the filter media bundle fibers in an embodiment of the invention.

FIG. 9 is a schematic cross-sectional view of a concentric bi-component fiber in an embodiment of the invention.

FIG. 10 is a schematic cross-sectional view of an eccentric bi-component fiber in an embodiment of the invention.

FIG. 11 is a schematic cross-sectional view a multi-component fiber in an embodiment of the invention.

FIG. 12 is a schematic cross-sectional view depicting first and second compression zones of compressible filter media in a filter media housing in an
5 embodiment of the invention.

FIG. 13A is a schematic cross-sectional view of a filter media housing including uncompressed filter media and a backwash removal device in an embodiment of the invention.

FIG. 13B is a schematic top plan view of a backwash removal device
10 along line I-I of FIG. 13A in an embodiment of the invention.

FIG. 14A is a schematic top plan view of a plurality of filter units within a large fluid containment in an embodiment of the invention.

FIG. 14B is a schematic cross-sectional view of a plurality of filter units along line II-II of FIG. 14A.

15

Detailed Description of the Invention

The present invention provides an apparatus and method for filtering fluids with compressible filter media contained in a flexible housing. In the described embodiments, fluid outside the housing compresses the housing and filter media;
20 however, it will be appreciated that a variety of external forces may be applied to the outer housing and compressible media to achieve the objectives of the invention in other embodiments. It will also be appreciated that although the invention is described in embodiments for top to down filtering of fluid, the

apparatuses and components described herein may be positioned such that the filtration may occur in other directions, and repositioning is within the scope of the invention.

5 The present invention thus provides improved filtration, and is particularly adapted for the filtration of stormwater, drinking water and wastewater. Those skilled in the art will further appreciate that in other embodiments the present invention is adapted for use with a variety of fluids and filtering applications.

Referring to FIG. 1, in an embodiment of the present invention a filter apparatus **10** includes an outer fluid container **15**. Outer fluid containment housings include concrete containers, earthen basins, natural water features (including a lake), and like environments in which fluid to be filtered may be contained. An influent pipe **20** provides fluid to be filtered into the outer container **15**. It will be appreciated that the influent pipe **20** may be located in a variety of positions (such as above or below the top of the filter) and or/include a plurality of
15 influent pipes **20**.

Within the outer container **15** an upright filter media housing **25** is provided. FIG. 1 depicts the filter media housing **25** comprising a flexible membrane in both expanded and compressed embodiments to demonstrate compressibility of the housing. The top of the filter media housing **25** includes an
20 upper perforated plate **30** to allow fluid to be filtered into the housing, as well as backwash fluid out of the housing, while retaining the filter media within housing (such as during backwash processes subsequently described).

A housing base **35** secures the filter media housing **25** at the bottom of the outer container **15**.

In one embodiment, the base may include baffles **40** that direct filtered fluid to an effluent pipe **45** carrying filtered fluid from the filter housing **25** out of the containment **15**. The baffles **40** may also direct air and make-up water to the center of lower perforated plate **50** during backwashing operations (FIG. 5).

Referring to FIGS. 14A and 14B, in other exemplary embodiments, the containment **15** may include a plurality of filter units **11** wherein the base may be a wall of an effluent channel/conveyance **45A** or a piping network underlying one or more filter units **11**. In such embodiments, the channel wall or piping serves as the base to support one or more filter units **11** in an upright position within the outer containment **15**. The integrated filter unit **11** into the conveyance **45A** may be provided without baffles **40**.

In a large containment environment as shown in FIGS. 14A and 14B, the underlying effluent conveyances (or piping) **45A** may all connect to a larger effluent conveyance **45B** for carrying off filtered fluid. In other embodiments underlying conveyances **45A** may be directed to other desired locations and conveyance points.

FIGS 14A and 14B, also show that one or more backwash pumps **72** may be provided for removing backwash fluid from the containment **15** following the backwash process (subsequently described).

In embodiments utilizing a plurality of filter units **11**, it will be appreciated that the containment **15** may include a large basin, natural feature, manmade

containments and the like, where a large quantity of fluid is to be filtered. It will also be appreciated each of the filter units 11 includes compressible media 60 and a filter media housing 25 and operates as subsequently described with reference to a single filter unit.

5 Referring again to FIG. 1, between the upper plate 30 and base 35, the lower perforated plate 50 allows filtered fluid to exit the flexible housing 25. The lower perforated plate 50 also supports filter media 60 (FIG. 2) within the housing 25.

With further reference to FIG. 2 and FIGS. 7-11, compressible filter media 10 60 is housed within the housing 25 between the upper perforated plate 30 and lower perforated plate 50. Although the filter bundles disclosed in U.S. Pat. No. 5,248,415 to Masuda et al. and U.S. Patent Application Publication No. US2003/0111431 are particularly adapted for use as filter media 60 in the present invention, a variety of compressible fibrous filter elements may be used.

15 In certain embodiments, the fibrous media 60 of the present invention improves upon the prior art through the use of multi-component fibers where two or more synthetic materials are used in the same fiber to achieve the physical characteristics such as specific gravity, resilience, chemical resistance, stiffness, fiber diameter, and the like. In other embodiments, the filter media fiber may 20 further include components with specifically desired performance characteristics such as specific pollutant removal capabilities. For example, oleophilic fiber components may be used in embodiments for attracting oil from fluid being filtered or hydrophobic fibers may be used to encourage water filtration. Those

skilled in the art will appreciate that a wide variety of other combinations of components in the filter media may be adapted for use in the present invention depending on the desired performance the type of fluid and pollutants being filtered.

5 In one embodiment to achieve a chemically resistant fibrous lump of low resilience and lower specific gravity, the fiber is manufactured with a nylon inner core and polypropylene outer cover.

 In another embodiment to obtain a heavier, more resilient lump **61** (FIGS. 7 and 8), the fiber is manufactured using a polyester inner core with a
10 polypropylene sheath.

 Referring to FIG. 9, in one embodiment the multi-component fiber is a bi-component fiber, wherein an inner fiber **65** and an outer fiber **67** (sheath) are provided/extruded in a generally concentric configuration.

 Referring to FIG. 10, in another embodiment the components are
15 generally eccentric with the inner component **65** being off-center. In such embodiment, subsequently described, the eccentric configuration permits heating of the fiber to produce crimping based on the resultant heat distortion.

 It will be appreciated that in alternative embodiments a plurality of inner fibers **65** may be contained in a sheath **67**, such as shown in FIG. 11. In such
20 embodiments, the plurality of inner fibers **65** may be the same or different component materials. It will also be appreciated that one or more additional outer sheaths could be provided in alternative embodiments to achieve specific pollutant removal as well as exhibit desired physical characteristics.

In various embodiments, core and sheath materials may include any combination of the following, or other synthetic fibers: polyester (PET), coPET, polylactic acid (PLA), polytrimethylene terephthalate, polycyclohexanediol terephthalate (PCT), polyethylene naphthalate (PEN); high density polyethylene (HDPE), linear low density polyethylene (LLDPE), polyethylene (PE),
5 polypropylene (PP), PE/PP copolymer, nylon, polyvinylidene fluoride (PVDF), polytetrafluoroethylene (PTFE) and polyurethane.

Referring to FIG. 6, the fibers used as filter media **60** are initially in the form of loosely packed elongated fibers **70** on spools **75**.

10 With continuing reference to FIG. 6, several bundles of elongated fibers **70** are brought together from the spools **75** using a reducing device **80**. The device **80** reduces the overall size of the fibers while a hog ring fastener/binding wire **85** or other similar clamp is applied. After the clamps are applied, the fiber bundles are cut at cut lines **90** between each clamp **85** to form a fibrous lump **61** (FIGS. 7
15 and 8).

In embodiments of the invention, the multi-component fibers can be crimped mechanically and/or by heating.

A mechanical crimping machine is used in one method. Following extrusion, the fibers are mechanically crimped along the length of the fibers to
20 produce crimped fiber. A second method is to produce the multi-component fiber **65** such that the core materials are placed eccentrically from the sheath **65** (FIG. 10). When heat is applied, the fiber materials distort differently resulting in a

helically shaped crimp. The amount of heat applied is dependent on the fiber materials.

Referring again to FIG. 2, during initial filling, fluid **22** to be filtered enters from the influent pipe **20** and fills the void **28** between the outer container **15** and flexible housing **25**. The air inlet **90** is off. The drain **95** is closed.

With continuing reference to FIG. 2, initial compression of the filter media is adjustable and can be set by the level of fluid and media inside the filter media housing **25** at the beginning of the filter run. After backwashing (see FIG. 5 and related description), the media is in a relatively uniform suspension with density equal to the number of filter media bundles **61** per volume of fluid within the flexible membrane **25**. A lower fluid level inside the flexible membrane **25** will result in a greater density of filter media **60** and thus a greater initial compression when the void space **28** begins to fill and the flexible membrane **25** compresses the filter media **60**. A higher fluid level left inside the flexible membrane **25** at the beginning of the filter cycle will result in a lower initial compression. Initial compression is shown in FIG. 2. During this initial filling, it will be appreciated that the flexible housing **25** is relatively expanded until the hydrostatic pressure outside the housing **25** exceeds the pressure within the housing **25**.

With further reference to FIGS. 3 and 12, fluid **22** rises above the upper perforated plate **30** of the flexible membrane housing **25**, the fluid **22** enters the top perforated plate **30** for filtering by the filter media **60**. The fluid being filtered **22** passes downward through the filter media **60** with particulates being removed from the fluid. It will be appreciated that, in general, larger particulates are

removed nearer the top of the filter bed with smaller particulates removed deeper in the media bed and as solids begin to bridge the voids between the media fibers a matting takes place resulting in removal of both fine and larger particles in the upper media zone (FIG. 12). It will also be appreciated that less
5 compression with media open to the fluid being filtered **22** results in the upper zone of the media bed and more compression results in the lower zone. Because of the compression zones, the filter bed becomes more effective in removing a larger amount of particulates per unit of media and protect the finer particulates from passing through the filter. The compression differential
10 described above between the upper and bottom zones of the media bed is created in the initial compression developed after backwashing or during initial filter operation.

With continuing reference to FIG. 12, initial compression shows the lower filter media bed **60B** to be compressed inward by the filter media housing **25**.
15 The upper filter media bed **60A** is relatively uncompressed as the housing **25**, in embodiments where the housing is a flexible membrane, remains tight and relatively inflexible at the upper portion of the housing **25** between upper plate **30** and a taper point **27**.

In other embodiments the filter media housing **25** may include a plurality
20 of components to achieve the similar effect of multiple compression zones. For example, the upper portion of the housing **25** may comprise a rigid element connected to a lower membrane (lower portion of housing **25**). The upper filter media **60A** in such embodiment would be uncompressed from the external fluid

as the rigid upper portion would not flex inward. The flexible lower portion of the filter membrane would be compressible by the outer fluid to generate compressed lower bed **60B**.

In still other embodiments, the housing **25** could include a lower housing
5 portion with hinged plate walls instead of a flexible membrane. In such
embodiments, the hinged wall could be provided with a hinge near taper point **27**,
wherein the upper portion of the housing **25** would be a relatively rigid
component. Such walls could be provided in a variety of shapes, including flat
wall plates with leak-resistant membranes or materials joining one plate to the
10 next plate. Sliding mechanisms may also be used for a portion of the housing to
compress inward. It will be appreciated that all such embodiments permit the
external fluid pressure to compress the lower portion of the housing and the
lower filter media bed **60B** inward.

In embodiments where the housing **25** is flexible, it may be constructed of
15 single or multi-ply membranes of chlorosulfonated polyethylene (Hypalon),
polyvinyl chloride (PVC), rubber, viton, polypropylene, polyethylene, vinyl,
neoprene, polyurethane and woven and non-woven fabrics. In embodiments
where rigid materials are used, such as those including an upper rigid portion or
including pivotable or sliding housing walls, construction materials could include
20 steel, stainless steel, other metals, reinforced and unreinforced plastics. It will be
appreciated, however, that the filter media housing **25** may be constructed of any
suitable material depending on the desired filtering use, types of fluids being
filtered, desired corrosive characteristics and the like.

It will also be appreciated that although the present invention is shown in embodiments with external fluid pressure generating compressive force against the housing **25** and filter media **60**, other external forces may also, or additionally, be used to compress the lower filter media bed **60B**. For example, 5 in other embodiments, the side walls of the housing **25** may be actuated in an inwardly pivotable or sliding manner through mechanical, electrical, hydraulic and similar operation. In other embodiments, inflatable components may be provided external to the housing and inflated in a balloon-like manner to press against the housing and compress the filter media.

10 Referring again to FIG. 12, the top surface of the filter media bed **60** includes space **62** (see also FIGS. 2-4) that is open and untouched by the upper perforated plate. In such embodiment, the upper filter media zone **60A** remains uncompressed by not only the housing **25**, but also avoids external top to down compression from the upper plate **30** because of spacing **62**. It will also be 15 appreciated that the initial compression with relatively uncompressed upper filter media bed **60A** with an open surface and the compressed lower filter media bed **60B** will result in greater particulate penetration than if the upper filter media bed **60A** were compressed or the entire bed were compressed. Finer particulates may therefore be captured in the lower media bed **60B** as greater penetration is 20 achieved. It is thus an object of the present invention to maximize fluid filtering efficiency.

Referring further to FIGS. 3 and 4, as filtration proceeds and more particulates are removed, the hydraulic head differential across the filter

becomes greater (FIG. 3 to FIG. 4) causing greater compression in the lower zone **60B** to prevent smaller particulates from passing through. There is also a slight upheaval of upper media zone **60A** as the lower zone **60B** compresses to allow more particulates to enter the filter media **60**. Compression of the filter media **60**, as described with reference to FIGS. 3 and 4, thus improves filtering as increasingly smaller and more particulate is removed in the filter media bed **60**.

In embodiments of the invention, the flexible housing **25** shape is also generally wider at the upper portion than at the lower portion of the housing **25**. It will be appreciated that in such embodiments, less filter media **60** is required at the bottom as the filter bed narrows to direct the fluid out of the housing **25** and the fluid **22** being filtered is "cleaner" toward the bottom. Further, the generally tapered embodiment provides additional filter benefits as the media is more loosely packed near the more "open" upper portion and is more densely packed nearer the bottom portion of the housing.

In other embodiments, it will be appreciated that in addition to or instead of tapering housing shapes, different compression levels may be created by higher media concentrations with lower inner fluid levels. Different filter materials and combinations of materials with desired physical properties may also be used to achieve different compression levels, including the layering of filter media with different densities, compressibility or other desired physical and performance characteristics to achieve a desired filter bed that may include one or more zones.

FIG. 3 shows the hydraulic head in the upstream portions outside the flexible housing **25** becoming greater than the downstream hydrostatic pressure. The hydraulic head differential is due to both the flow stream through the filter media **60** and the build-up of particles on the filter media **60**, resulting in increasing upstream fluid level as solids are removed (FIGS. 3 and 4). As the hydrostatic pressure outside the filter media housing **25** becomes greater than the hydrostatic pressure inside the housing **25**, the housing **25** is further compressed inward, thereby further compressing the filter media **60**. In embodiments of the invention, the housing **25** and filter media **60** are compressed in a direction non-parallel, including generally perpendicular in some embodiments (FIGS. 2-4 and 12), to the direction of the fluid flow through the filter media. And as also shown in FIG. 12, and previously described, a plurality of compression zones may be established, such as lower portion of the filter media bed **60B** being compressed to remove finer particulates and protect the filter media bed **60** from particle breakthrough.

Referring to FIG. 4, an embodiment of the invention is shown when the filtration cycle has reached its latter stages and/or during a period of peak upstream fluid flow. The latter stage of the filtration cycle is reached when the filter media **60** captures its maximum particle load, and the depth of fluid **22** over the top of the upper perforated plate **30** reaches its maximum fluid level.

In one embodiment of the invention, when the fluid **22** over the filter apparatus **10** reaches its maximum fluid level, closing the influent **20** stops the filter cycle. In this embodiment the backwashing cycle (FIG. 5) is initiated.

In another embodiment of the invention where an overflow pipe **100** is provided, the filter cycle continues whereby fluid **22** is both filtered through the media bed **60** and a portion of the fluid bypasses the filter and is discharged from the outer housing **15** along with the filtered effluent **45**. It will be appreciated that
5 filtration of wet weather flows, such as treatment of stormwater or treatment of wet weather discharges from sewer systems, can be designed to remove a specific particle load according to a desired need for a particular event, and after the load is reached or the design flow rate is reached, excess flows and excess particle loads may be discharged from the filter.

10 FIG. 5 shows the filter media **60** being backwashed to remove particulate build up. During a backwash operation fluid entry from the influent pipe **20** is stopped. Make-up water **23** is introduced into the filter effluent pipe **45** or to an open-close connection valve to the outer section of the housing base portion **35**. A backwash outlet, such as a backwash pump discharge **105** connected to a
15 backwash pump **72** (FIG. 14A), can be used to remove the backwashed particles from the containment housing **15** or the backwashed fluid can be removed from the containment **15** by opening a drainpipe **95**. During backwash the fluid level within the containment housing **15** is lower than the water level within the filter media housing **25** causing the housing **25** to expand.

20 In the backwash cycle, an air inlet **90**, provides air from a blower at the base portion **35** or under the lower perforated plate **50**. It will be appreciated that the backwashed fluid containing the concentrated particulates from the fluid to be filtered **22** is typically transferred to a sanitary sewer system for further treatment,

removed by vacuum vehicle equipment for transport to other facilities for further process or by further processing the backwash fluid on-site by other concentrating and dewatering processes.

5 The air from the air inlet **90** enters the center section of the base **35** and rises through the center of the lower perforated plate **50** and up through the center of the filter media **60**. The upward center air flow causes the filter media **60** to circulate within the expanded filter media housing **25** during the washing cycle. Circulation of the filter media **60** causes the media **60** to collide with the upper perforated plate **35** and with other media bundles **60**, helping particulates
10 to dislodge. The lower specific gravity of the air/fluid mixture or the hydraulic head of the backwash water within the housing **25** causes the fluid level within the housing **25** to rise and flow over the upper perforated plate **30** into the void **28** inside of the outer container **15** and outside the housing **25**. The backwash fluid exits containment **15** by either gravity drainage through drain **95** or pumping
15 through outlet **105**.

Another embodiment, shown in FIGS. 13A and 13B, includes backwash removal device **200** having troughs **201**, placed on the upper perforated plate **30**. In this embodiment, troughs **201** form a donut-shape around the center of the air inlet on the upper perforated plate **30**. The troughs **201** receive the backwash
20 fluid with concentrated particulates as the backwash fluid rises above the perforated plate **30** (through the action of centrally directed air) and is directed through the radial troughs **201** to the void **28**, thus minimizing particulate recirculation during the backwash mode. It can be appreciated that the quicker

the backwash fluid is separated from the circulating media, the less make-up water is required to clean the filter and the shorter the backwashing cycle time. It can also be appreciated that water level in the center of the upper plate **30** is at the highest level caused by the central rising air and this hydraulic head is used
5 to drive the backwash fluid through the radial troughs **201** into the void **28** for removal.

In another embodiment, a drain **95** is provided at the bottom of the outer container **15**. The drain **95** can also be opened to remove fluid from inside the outer container **15**, such as following backwashing. Further, the void **28** between
10 the outer container **15** and housing **25** can be cleaned, and the drain **95** opened to remove the cleaning fluid. It will be appreciated that a plurality of drains **95** may also be provided.

In another embodiment, the backwash removal device **200** can be designed with troughs **201** being enclosed, for example, using pipes to carry
15 backwash water out of the outer containment **15**. It can be appreciated that in certain outer containment structures such as earthen basins with permanent lower water levels or natural water features (such as lakes), the outer containment **15** would not be drained and it may be desired that backwash water be discharged outside of the outer containment **15**. It can be further appreciated
20 that in this application the compressible media housing **25** may be actuated inwards or outwards by an inflatable balloon or similar alternative method as described previously. It can be further appreciated that in an application where

the outer containment **15** is a natural water feature with a fixed water level, the fluid inlet to the filter may be closed when backwashing occurs.

Accordingly, while the invention has been described with reference to the structures and processes disclosed, it is not confined to the details set forth, but
5 is intended to cover such modifications or changes as may fall within the scope of the following claims.